

NU-FLAME® FLAME RETARDANT CLEAR OVERCOAT

DESCRIPTION:	Nu-Flame Clear Overcoat is a clear varnish finish coating with flame retardant qualities.
INTUMESCENT FIRE PROTECTION:	To complete the system and protect the Nu-Flame Intumescent Varnish.
FIRE TESTING:	Tested to BS476 Part 7 Class 1 surface spread of flame and BS476 Part 6 Fire propagation. Designated Class '0' to current Building Regulations when Used in conjunction with Nu-Flame Intumescent Varnish
ADVANTAGES:	Protects the intumescent varnish when subjected to abrasion humidity, heat and general wear and tear.
COLOUR RANGE:	Clear gloss, satin or matt finishes are available.
PACK SIZE:	Single component product, supplied in 5 and 25 litre cans.
COVERAGE RATE:	Should be applied at a coverage rate 12 m ² per litre. Two coats required.
DRYING TIMES:	Touch dry... 3 hours. Overcoat... 12 hours
PREPARATION:	Abrade all surfaces to provide a key. Ensure surface is clean and free from surface moisture.
APPLICATION:	By brush/roller or conventional spray Maximum relative humidity during application and drying 75%. Minimum temperature during application and drying 8°C. Minimum surface temperature 3°C above dew point.
EQUIPMENT CARE:	All equipment should be cleaned with white spirit immediately after use.
STORAGE:	Store away from direct sunlight and sources of heat. Protect from frost.
SHELF LIFE:	12 months (in original sealed container).
HEALTH & SAFETY:	Refer to health and safety sheets.