

PRODUCT DATA SHEET HPC 136

CI/SFB Vv4

January 2012

NU-BASE® ACRYLIC BLOCK SEAL

- DESCRIPTION:** Nu-Base Acrylic Block Seal is a specifically formulated quick drying acrylic sealant designed to protect concrete and block paving against the ingress of water, dirt, oil, grease and a wide range of chemicals.
- ADVANTAGES:** Single pack ready for immediate use. Will consolidate jointing sand and help stop the growth of moss and weeds, and will provide a cost effective hard wearing, quick drying, durable and chemical resistant finish.
- USES: FeRFA Class Type 1** Nu-Base Acrylic Block Seal is for use on concrete and block paving.
- COLOUR RANGE:** Clear
- PACK SIZE:** Single component product, supplied in 25 litre cans.
- VOLUME SOLIDS:** 40%
- COVERAGE RATE:** This is dependent upon the surface porosity. Average coverage rate is in the region of 3-5 m² per litre.
- DRYING TIME:** Touch dry.....40 Minutes@ 20°C.
Overcoat.....1 hour.
- PREPARATION:** Ensure surfaces to be treated are clean, free from contamination and dry. All loose materials should be swept away and laitance removed by etching with Nu-Base Acid Etch. The surface should then be washed off to provide a clean neutral surface and allowed to dry overnight.
- APPLICATION:** By brush/roller or low pressure spray
- EQUIPMENT CARE:** All equipment should be cleaned with Xylene. Conventional thinners and brush cleaners are not effective.
- STORAGE:** Store away from direct sunlight and sources of heat. Protect from frost.
- SHELF LIFE:** 12 months (in original sealed container).
- HEALTH & SAFETY:** Refer to health and safety sheets.



HYDRON
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494