

PRODUCT DATA SHEET HPC 129

CI/SFB Vv4

January 2010

NU-BASE® CHLORINATED RUBBER

DESCRIPTION:	Nu-Base Chlorinated Rubber Floor paint is a fast drying finish based on Chlorinated rubber resin, giving good adhesion and exterior durability.
ADVANTAGES:	When fully dry, the paint has good resistance to petrol, paraffin and mineral oil spillage. Nu-Base Chlorinated Rubber Floor paint is ideally suited for brush or roller application over large areas.
USES:	For use on metal and concrete. Ideal for use in swimming and paddling pools.
COLOUR RANGE:	Selected colour range
PACK SIZE:	Single component product, supplied in 5 and 25 litre cans.
VOLUME SOLIDS:	40%
COVERAGE RATE:	10 – 12 m ² per litre.
DRYING TIME:	Touch dry.....30-45 minutes @ 20°C Hard dry.....12 hours. Full properties.....7 days.
PREPARATION:	All surfaces to be coated should be clean, dry and free from oil and grease etc. Ideally the substrate should be shot-blasted, mechanically abraded or acid etched with all loose, flaking materials and any laitance removed.
APPLICATION:	By brush/roller. Paints should be used as supplied, thinning is not recommended.
EQUIPMENT CARE:	All equipment should be cleaned with Nu-Base Chlorinated Rubber Thinners. Conventional thinners and brush cleaners are not effective.
STORAGE:	Recommended storage is in a cool, dry place with temperatures between 10-15 °C, and in accordance with the Highly Flammable Liquids and Liquefied Petroleum Gases Regulations 1972.
SHELF LIFE:	12 months (in original sealed container).
HEALTH & SAFETY:	Refer to health and safety sheets.



HYDRON
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494