

PRODUCT DATA SHEET HPC 131

CI/SFB Vv4

January 2012

NU-BASE® CHLORINATED RUBBER LINE PAINT

- DESCRIPTION:** Nu-Base Chlorinated Rubber Line Paint is a fast drying finish based on Chlorinated rubber resin, giving good adhesion and exterior durability.
- ADVANTAGES:** When fully dry, the paint has good resistance to petrol, paraffin and mineral oil spillage.
- USES:** For use on concrete, weathered tarmac, brick, paving and wood
Ideal for use in car parks, roads, runways and factory floors.
- COLOUR RANGE:** Selected colour range
- PACK SIZE:** Single component product, supplied in 5 and 20 litre cans.
- VOLUME SOLIDS:** 50%
- COVERAGE RATE:** 3.5m² per litre.
- DRYING TIME:** Touch dry.....15 minutes @ 20°C
Overcoat.....1hour minimum @ 20°C
- PREPARATION:** All surfaces to be coated should be clean, dry and free from oil and grease etc. Ideally the substrate should be shot-blasted, mechanically abraded or acid etched with all loose, flaking materials and any laitance removed.
- APPLICATION:** By brush, roller or spray. Paints should be used as supplied.
If thinning, use no more than 10% of Nu-Base Chlorinated Rubber Thinners.
Ballotini beads may be added to the wet film surface immediately after application, if added reflectance is required.
- EQUIPMENT CARE:** All equipment should be cleaned with Nu-Base Chlorinated Rubber Thinners. Conventional thinners and brush cleaners are not effective.
- STORAGE:** Recommended storage is in a cool, dry place with temperatures between 5-30 °C,
- SHELF LIFE:** 12 months (in original sealed container).
- HEALTH & SAFETY:** Refer to health and safety sheets.



HYDRON
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494