

PRODUCT DATA SHEET HPC 126

CI/SFB Vv4

January 2012

NU-BASE® H.B EPOXY FLOOR FINISH

DESCRIPTION:	Nu-Base H.B. Epoxy Floor Finish is a two-pack water based resin. For use in most industrial floors including concrete and wood and provides a decorative dust-free finish. Being odour free and non-tainting is ideal for use in food industry, dairies, and breweries.
ADVANTAGES:	Nu-Base H.B. Epoxy Floor Finish, has excellent resistance against distilled water, dilute minerals, acids and alkalis. Aggregates can be incorporated for improved slip resistance and wearing properties.
USES: FeRFA Class Type 3	Nu-Base H.B. Epoxy Floor Finish is suitable for us in garages, workshops, warehouses and general industrial usage.
COLOUR RANGE:	Selected colour range.
PACK SIZE:	Two component product, supplied in 5 & 10 KG units.
VOLUME SOLIDS:	100%
COVERAGE RATE:	3-4 m ² / KG
DRYING TIME:	Touch dry.....6 hours @ 20°C. Overcoat.....24 hours. Full Cure.....7 days.
POT LIFE	20 minutes @ 20°C
PREPARATION:	All surfaces to be coated should be clean, dry and free from oil and grease etc. Ideally the substrate should be shot-blasted, mechanically abraded or acid etched with all loose, flaking materials and any laitance removed.
APPLICATION:	By brush/roller
EQUIPMENT CARE:	All equipment should be cleaned with water immediately after use.
STORAGE:	Store away from direct sunlight and sources of heat. Protect from frost.
SHELF LIFE:	12 months (in original sealed container).
HEALTH & SAFETY:	Refer to health and safety sheets.



HYDRON
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494