

# PRODUCT DATA SHEET HPC 126

CI/SFB Vv4

January 2010

## NU-BASE® H.B EPOXY FLOOR FINISH

<b>DESCRIPTION:</b>	Nu-Base H.B. Epoxy Floor Finish is a two-pack water based resin. For use in most industrial floors including concrete and wood and provides a decorative dust-free finish. Being odour free and non-tainting is ideal for use in food industry, dairies, and breweries.
<b>ADVANTAGES:</b>	Nu-Base H.B. Epoxy Floor Finish, has excellent resistance against distilled water, dilute minerals, acids and alkalis. Aggregates can be incorporated for improved slip resistance and wearing properties.
<b>USES: FeRFA Class Type 3</b>	Nu-Base H.B. Epoxy Floor Finish is suitable for us in garages, workshops, warehouses and general industrial usage.
<b>COLOUR RANGE:</b>	Selected colour range.
<b>PACK SIZE:</b>	Two component product, supplied in 5 & 10 KG units.
<b>VOLUME SOLIDS:</b>	100%
<b>COVERAGE RATE:</b>	3-4 m <sup>2</sup> / KG
<b>DRYING TIME:</b>	Touch dry.....6 hours @ 20°C. Overcoat.....24 hours. Full Cure.....7 days.
<b>POT LIFE</b>	20 minutes @ 20°C
<b>PREPARATION:</b>	All surfaces to be coated should be clean, dry and free from oil and grease etc. Ideally the substrate should be shot-blasted, mechanically abraded or acid etched with all loose, flaking materials and any laitance removed.
<b>APPLICATION:</b>	By brush/roller
<b>EQUIPMENT CARE:</b>	All equipment should be cleaned with water immediately after use.
<b>STORAGE:</b>	Store away from direct sunlight and sources of heat. Protect from frost.
<b>SHELF LIFE:</b>	12 months (in original sealed container).
<b>HEALTH &amp; SAFETY:</b>	Refer to health and safety sheets.



**HYDRON**  
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494