

PRODUCT DATA SHEET HPC 120

CI/SfB Vv4

January 2012

NU-BASE® P.U FLOOR SEAL

DESCRIPTION:	Nu-Base P.U. Floor Seal is a moisture cured polyurethane sealer designed to dustproof and protect concrete floors against the ingress of dirt, oil, grease and a wide range of chemicals.
ADVANTAGES:	Single pack ready for immediate use. Provides a cost effective hardwearing and chemical resistant finish.
USES: FeRFA Class Type 1	Nu-Base P. U. Floor Seal is for use on cement based screeds and concrete sub-floors, providing a clear finish.
COLOUR RANGE:	Clear
PACK SIZE:	Single component product, supplied in 5 and 25 litre cans.
VOLUME SOLIDS:	40%
COVERAGE RATE:	This is dependant upon the surface porosity. Average coverage rate is in the region of 6 m ² per Kg.
DRYING TIME:	Touch dry.....3 hours @ 20°C. Overcoat.....4 hours.
PREPARATION:	Ensure surfaces to be treated are clean, free from contamination and dry. All loose materials should be swept away and laitance removed by etching with Nu-Base Acid Etch. The surface should then be washed off to provide a clean neutral surface and allowed to dry overnight.
APPLICATION:	By brush/roller
EQUIPMENT CARE:	All equipment should be cleaned with Nu-Base P.U. Thinners. Conventional thinners and brush cleaners are not effective.
STORAGE:	Store away from direct sunlight and sources of heat. Protect from frost.
SHELF LIFE:	12 months (in original sealed container).
HEALTH & SAFETY:	Refer to health and safety sheets.



HYDRON
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494