

PRODUCT DATA SHEET HPC 128

CI/SFB Vv4

January 2012

NU-BASE® P.U PIGMENTED FLOOR FINISH

- DESCRIPTION:** Nu-Base P.U. Floor Finish is a two pack solvent-based polyurethane resin. For use on most industrial floors and is also suitable for application on steel and aluminium
- ADVANTAGES:** Nu-Base P.U. Floor Finish, offers maximum chemical resistance which is light fast and flexible. The system is resistant to high temperatures up to 150°C.
- USES: FeRFA Class Type 2** For use in manufacturing areas, laboratories, chemical plants aircraft hangers and all areas where a high chemical resistant finish is essential.
- COLOUR RANGE:** Selected colour range.
- PACK SIZE:** Two-component product, supplied in 5 litre units.
- VOLUME SOLIDS:** 45 - 60%
- COVERAGE RATE:** 8 m² per Litre @ 75 micron thickness.
- DRYING TIME:** Touch dry.....2 hours @ 20°C.
Overcoat.....2 - 4 hours.
Full Cure.....5 days @ 20°C.
- PREPARATION:** All surfaces to be coated should be clean, dry and free from oil and grease etc. Ideally the substrate should be shot-blasted, mechanically abraded or acid etched with all Loose, flaking materials and any laitance removed.
- APPLICATION:** By brush/roller.
- EQUIPMENT CARE:** All equipment should be cleaned with Nu-Base P.U Thinners. Conventional thinners and brush cleaners are not effective.
- STORAGE:** Store away from direct sunlight and sources of heat.
Protect from frost.
- SHELF LIFE:** 12 months (in original sealed container).
- HEALTH & SAFETY:** Refer to health and safety sheets.



HYDRON
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494