

PRODUCT DATA SHEET HPC 122

CI/SFB Vv4

January 2010

NU-BASE® S.P FLOOR PAINT

DESCRIPTION:	Nu-Base Single Pack Floor Paint is a fast drying floor paint based on a polyurethane modified alkyd resin.
ADVANTAGES:	Excellent decorative appearance with resistance to a wide range of mild chemicals, solvents and detergents.
USES: FeRFA Class Type 1	Specially recommended for interior use on coated and uncoated concrete, stone, metal and wooden floor surfaces.
COLOUR RANGE:	Available in 3 shades of Grey, Tile Red and Bottle Green.
PACK SIZE:	Single component product, supplied in 5 and 25 litre cans.
VOLUME SOLIDS:	50%
COVERAGE RATE:	8 - 10m ² per litre.
DRYING TIME:	Touch dry.....2 - 4 hours @ 20°C. Overcoat.....16 - 24 hours.
PREPARATION:	Ensure surfaces to be treated are clean, free from contamination and dry. All loose materials should be swept away and laitance removed by etching with Nu-Base Acid Etch. The surface should then be washed off to provide a clean neutral surface and allowed to dry overnight.
APPLICATION:	By brush/roller or airless spray.1st coat thinned with 10% Nu-Base S.P. Thinners. Allow to dry. This should then be overcoated with at least one full coat.
EQUIPMENT CARE:	All equipment should be cleaned with Nu-Base S.P. Thinners. Conventional thinners and brush cleaners are not effective.
STORAGE:	Store away from direct sunlight and sources of heat. Protect from frost.
SHELF LIFE:	12 months (in original sealed container).
HEALTH & SAFETY:	Refer to health and safety sheets.



HYDRON
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494