

PRODUCT DATA SHEET HPC 124

CI/SFB Vv4

January 2012

NU-BASE® W.B CLEAR SEAL

DESCRIPTION:	Nu-Base W.B. Clear Seal is a two-pack water based epoxy resin. For sealing concrete or for use where a primer is required prior to the application of W.B. or H.B. Epoxy Finish.
ADVANTAGES:	Nu-Base W.B. Clear Seal has good chemical resistance. Will not support fungus or bacterial growth and is therefore suitable for application in food production areas, hospitals etc.
USES: FeRFA Class Type 1	Nu-Base H.B. Epoxy Floor Finish is suitable for us in garages, workshops, warehouses and general industrial usage.
COLOUR RANGE:	Clear
PACK SIZE:	Two component product, supplied in 5 & 10 KG units.
VOLUME SOLIDS:	50%
COVERAGE RATE:	This is dependant upon the surface porosity. Average coverage rate is in the region of 6 m ² per Kg.
DRYING TIME:	Touch dry.....8 hours @ 20°C. Overcoat.....24 - 48 hours.
POT LIFE	Full Cure.....7 days. 1 – 1.5 Hours @ 20°C
PREPARATION:	Ensure surfaces to be treated are clean, free from contamination and dry. All loose materials should be swept away and laitance removed by etching with Nu-Base Acid Etch. The surface should then be washed off to provide a clean neutral surface and allowed to dry overnight.
APPLICATION:	By brush/roller
EQUIPMENT CARE:	All equipment should be cleaned with water immediately after use.
STORAGE:	Store away from direct sunlight and sources of heat. Protect from frost.
SHELF LIFE:	12 months (in original sealed container).
HEALTH & SAFETY:	Refer to health and safety sheets.



HYDRON
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494