

# PRODUCT DATA SHEET HPC 124

CI/SFB Vv4

January 2010

## NU-BASE® W.B CLEAR SEAL

<b>DESCRIPTION:</b>	Nu-Base W.B. Clear Seal is a two-pack water based epoxy resin. For sealing concrete or for use where a primer is required prior to the application of W.B. or H.B. Epoxy Finish.
<b>ADVANTAGES:</b>	Nu-Base W.B. Clear Seal has good chemical resistance. Will not support fungus or bacterial growth and is therefore suitable for application in food production areas, hospitals etc.
<b>USES: FeRFA Class Type 1</b>	Nu-Base H.B. Epoxy Floor Finish is suitable for us in garages, workshops, warehouses and general industrial usage.
<b>COLOUR RANGE:</b>	Clear
<b>PACK SIZE:</b>	Two component product, supplied in 5 & 10 KG units.
<b>VOLUME SOLIDS:</b>	50%
<b>COVERAGE RATE:</b>	This is dependant upon the surface porosity. Average coverage rate is in the region of 6 m <sup>2</sup> per Kg.
<b>DRYING TIME:</b>	Touch dry.....8 hours @ 20°C. Overcoat.....24 - 48 hours.
<b>POT LIFE</b>	Full Cure.....7 days. 1 - 1.5 Hours @ 20°C
<b>PREPARATION:</b>	Ensure surfaces to be treated are clean, free from contamination and dry. All loose materials should be swept away and laitance removed by etching with Nu-Base Acid Etch. The surface should then be washed off to provide a clean neutral surface and allowed to dry overnight.
<b>APPLICATION:</b>	By brush/roller
<b>EQUIPMENT CARE:</b>	All equipment should be cleaned with water immediately after use.
<b>STORAGE:</b>	Store away from direct sunlight and sources of heat. Protect from frost.
<b>SHELF LIFE:</b>	12 months (in original sealed container).
<b>HEALTH &amp; SAFETY:</b>	Refer to health and safety sheets.



**HYDRON**  
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494