

PRODUCT DATA SHEET HPC 125

CI/SFB Vv4

January 2010

NU-BASE[®] W.B EPOXY FLOOR FINISH

DESCRIPTION:	Nu-Base W.B. Epoxy Floor Finish is a two-pack water based resin. For use in most industrial floors including concrete and wood and provides a decorative dust-free finish. Being odour free and non-tainting is ideal for use in food industry, dairies, and breweries.
ADVANTAGES:	Nu-Base W.B. Epoxy Floor Finish has good chemical resistance. Will not support fungus or bacterial growth and is therefore suitable for application in food production areas, hospitals etc.
USES: FeRFA Class Type 2	Nu-Base W.B. Epoxy Floor Finish is suitable for us in garages, workshops, warehouses and general industrial usage.
COLOUR RANGE:	Selected colour range.
PACK SIZE:	Two component product, supplied in 5 & 10 KG units.
VOLUME SOLIDS:	50%
COVERAGE RATE:	7-8 m ² / KG
DRYING TIME:	Touch dry.....8 hours @ 20°C. Overcoat.....24 – 48 hours. Full Cure.....7 days.
POT LIFE	1 – 1.5 hours @ 20°C
PREPARATION:	All surfaces to be coated should be clean, dry and free from oil and grease etc. Ideally the substrate should be shot-blasted, mechanically abraded or acid etched with all loose, flaking materials and any laitance removed.
APPLICATION:	By brush/roller or spray.
EQUIPMENT CARE:	All equipment should be cleaned with water immediately after use.
STORAGE:	Store away from direct sunlight and sources of heat. Protect from frost.
SHELF LIFE:	12 months (in original sealed container).
HEALTH & SAFETY:	Refer to health and safety sheets.



HYDRON
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494