

PRODUCT DATA SHEET HPC 40&46

CI/SFB Vv4

January 2010

NU-CRYL® A.G.

DESCRIPTION:

Nu-Cryl A.G. is a unique, clear, hydrophobic acrylic coating system.

ADVANTAGES:

Nu-Cryl A.G. will not noticeably change the appearance of the substrate. Due to its excellent stain resistant and water repellent qualities, dirt, pollution, and even graffiti can be removed from the treated surface.

The system gives long life graffiti and environmental protection. It has outstanding resistance to weathering and ultra-violet degradation, and no reapplication is required after graffiti removal. **Satisfies Class '0' requirements of current Building Regulation.**

USES:

For use on brickwork, concrete, natural stone, reconstructed stone and blockwork, marble and terrazzo. Compatible with concrete surfaces treated with Silane. Allow 72 hours to lapse before overcoating surfaces treated with Silane.

COLOUR RANGE:

HPC 40

Nu-Cryl AG

For porous substrates
Clear, invisible.

HPC 46

Nu-Cryl AG Extra

For dense low porosity substrates
Clear, invisible.

PACK SIZE:

5 L & 25 L Drums.

5 L & 25 L Drums.

COVERAGE RATE:

Average coverage rates:

DRYING TIME:

Sandstone.....5m²/litre
Facing brickwork. 5m²/litre
Concrete.....5m²/litre
Concrete blockwork 3m²/litre
Reconstructed stone 3m²/litre
Touch dry:.....4 hours
Waterproof:.... 24-48 hours
Overcoat:..... Wet on Wet

Granite.....15m²/litre
Marble.....13m²/litre
Terrazzo.....8m²/litre
Engineering brick....8m²/litre
Polished concrete....8m²/litre
Touch dry:.....2-3 hours
Waterproof:.....24 hours
Full cure.....5 days

PREPARATION:

Ensure surfaces to be treated are clean, free from contamination and dry. Treat all areas affected by organic growth with Hydron SS1 Sterilising Solution.

APPLICATION:

Application by low pressure spray or by brush/roller taking care to avoid any sagging. Application on vertical surfaces should be to full saturation commencing at the bottom and working upwards. One application is normally required, however on porous substrates a second application may be required.

Apply the second application in the same manner immediately after the first application, taking care not to allow the first application to dry out. Do not apply at temperatures below 5°C. Shake container well before use.

EQUIPMENT CARE:

All equipment should be cleaned with water immediately after use.

STORAGE:

Store away from direct sunlight and sources of heat. Protect from frost.

SHELF LIFE:

12 months (in original sealed container).

HEALTH & SAFETY:

Refer to health and safety sheets.



HYDRON
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494