

# PRODUCT DATA SHEET HPC 47

CI/SIB Vv4

January 2011

## NU-CRYL® WRS COLOUR ENHANCER

- DESCRIPTION:** Nu-Cryl W.R.S Colour Enhancer is a unique water based acrylic copolymer oil and water repellent treatment that lifts the true colour of the substrate. .
- ADVANTAGES:** Due to its excellent water repellent qualities, reduces penetration of oil and water, frost damage and organic growth. Conforms to BS 6477:1992. Enhances the natural colour of the substrate. Stain and dirt resistant. Non-stick and allows easy chewing gum removal. Will not affect the original colour of the substrate. Highly resistant to weathering and UV exposure. Moisture vapour permeable. Unaffected by freeze/thaw cycles.
- USES:** For use on walls and floors such brickwork, concrete, natural stone, reconstructed stone and blockwork, granite, marble and terrazzo.
- COLOUR RANGE:** Milky White. Dries colourless after application. Available in matt and satin finishes.
- PACK SIZE:** Single component product supplied in 5 or 25 Litre drums.
- COVERAGE RATE:** This is dependent upon the porosity of the substrate.
- DRYING TIME:** Average coverage rate between 6 – 10m<sup>2</sup>/Ltr  
Touch dry:.....4 hours.  
Waterproof:.....24-48 hours.
- PREPARATION:** Ensure surfaces to be treated are clean, free from contamination and dry. Treat all areas affected by organic growth with Hydron SS1 Sterilising Solution.
- APPLICATION:** Shake container well before use. Apply by brush, roller or spray. The surface to be treated should be impregnated up to saturation point. Two applications required (wet on wet) Do not apply at temperatures below 5°C.
- EQUIPMENT CARE:** All equipment should be cleaned with water immediately after use.
- STORAGE:** Store away from direct sunlight and sources of heat. Protect from frost.
- SHELF LIFE:** 12 months (in original sealed container).
- HEALTH & SAFETY:** Refer to health and safety sheets.



**HYDRON**  
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494