

PRODUCT DATA SHEET HPC 41&42

CI/SFB Vv4

January 2010

NU-CRYL® WRS.

DESCRIPTION:	Nu-Cryl W.R.S. is a unique acrylic oil and water repellent treatment.	
ADVANTAGES:	Due to its excellent water repellent qualities, reduces penetration of oil and water, frost damage and organic growth. Stain and dirt resistant. Non-stick and allows easy chewing gum removal. Conforms to BS 6477:1992. Will not affect the original colour of the substrate. Highly resistant to weathering and UV exposure. Moisture vapour permeable. Non-glossy appearance. Unaffected by freeze/thaw cycles. One application required reducing labour costs.	
USES:	For use on brickwork, concrete, natural stone, reconstructed stone and blockwork, granite, marble and terrazzo. May also be used on wood.	
COLOUR RANGE:	HPC 41 Nu-Cryl WRS For porous vertical walls and façades. Clear, invisible.	HPC 42 Nu-Cryl WRS Extra For dense surfaces subject to heavy wear such as pedestrian areas. Clear, invisible.
PACK SIZE:	5 L & 25 L Drums.	5 L & 25 L Drums.
COVERAGE RATE:	Average coverage rates:	
	Sandstone.....5m ² /litre Facing brickwork. 5m ² /litre Concrete.....5m ² /litre Concrete blockwork 3m ² /litre Reconstructed stone 3m ² /litre	Granite.....15m ² /litre Marble.....13m ² /litre Block Paving.....8m ² /litre Pre-cast Slabs....8m ² /litre Terrazzo8m ² /litre
DRYING TIME:	Touch dry:.....4 hours Waterproof:.... 24-48 hours	Touch dry:.....2-3 hours Waterproof:.....24 hours
PREPARATION:	Ensure surfaces to be treated are clean, free from contamination and dry. Treat all areas affected by organic growth with Hydron SS1 Sterilising Solution.	
APPLICATION:	Impregnation to be applied by flood-coating method using a low-pressure spray equipment of the knapsack type, or by brush/roller. Application on vertical surfaces should be to full saturation commencing at the bottom and working upwards. Two applications are required on wood with only one application required on masonry, brickwork etc. Do not apply at temperatures below 5°C. Shake container well before use.	
EQUIPMENT CARE:	All equipment should be cleaned with water immediately after use.	
STORAGE:	Store away from direct sunlight and sources of heat. Protect from frost.	
SHELF LIFE:	12 months (in original sealed container).	
HEALTH & SAFETY:	Refer to health and safety sheets.	



HYDRON
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494