

PRODUCT DATA SHEET HPC 110

CI/SFB Vv4

January 2010

NU-FLAME® A.G COLOURCOAT

DESCRIPTION:	Nu-Flame A.G. Colour Coat is a pigmented, smooth, non-toxic, water soluble urethane coating, providing an easy to clean, graffiti resistant surface.
ADVANTAGES:	Being a water soluble product this is safe for internal applications. U. V. Stable
USES:	Final coat to the Nu-Flame Fire Protection Coating for walls and ceilings.
COLOUR RANGE:	BS 4800 pastel shades
PACK SIZE:	Two component product, supplied in 5 litre cans.
VOLUME SOLIDS:	47%
COVERAGE RATE:	10 m ² per litre
DRYING TIME:	Touch :4 hours
PREPARATION:	Ensure surfaces to be treated are clean, free from contamination and dry.
APPLICATION:	By brush/roller or Airless Spray
EQUIPMENT CARE:	All equipment should be cleaned with water immediately after use
STORAGE:	Store away from direct sunlight and sources of heat. Protect from frost.
SHELF LIFE:	12 months (in original sealed container).
HEALTH & SAFETY:	Refer to health and safety sheets.



HYDRON
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494