

# PRODUCT DATA SHEET HPC 97

CI/SFB Vv4

January 2012

## NU-FLAME® CLEAR OVERCOAT

<b>DESCRIPTION:</b>	Nu-Flame Clear Overcoat is a clear varnish finish coating with flame retardant qualities. To complete the system and protect the Nu-Flame Intumescent Varnish.
<b>ADVANTAGES:</b>	Protects the intumescent varnish when subjected to abrasion humidity, heat and general wear and tear.  Tested to BS476 Part 7 Class 1 surface spread of flame and <b>BS476 Part 6 Fire propagation. Designated Class '0' to current Building Regulations when used in conjunction with Nu-Flame Intumescent Varnish.</b>
<b>COLOUR RANGE:</b>	Clear gloss, satin or matt finishes are available
<b>PACK SIZE:</b>	Single component product, supplied in 5 litre cans.
<b>COVERAGE RATE:</b>	Should be applied at a coverage rate 12 m <sup>2</sup> per litre. Two coats required.
<b>DRYING TIME:</b>	Touch dry...3 hours.                      Overcoat...12 hours
<b>PREPARATION:</b>	Abrade all surfaces to provide a key. Ensure surface is clean and free from surface moisture.
<b>APPLICATION:</b>	By brush/roller or conventional spray Maximum relative humidity during application and drying 75%. Minimum temperature during application and drying 8°C. Minimum surface temperature 3°C above dew point.
<b>EQUIPMENT CARE:</b>	All equipment should be cleaned with water immediately after use
<b>STORAGE:</b>	Store away from direct sunlight and sources of heat. Protect from frost.
<b>SHELF LIFE:</b>	12 months (in original sealed container).
<b>HEALTH &amp; SAFETY:</b>	Refer to health and safety sheets.



**HYDRON**  
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494