

PRODUCT DATA SHEET HPC 99

CI/SfB Vv4

January 2012

NU-FLAME® FR COLOURCOAT

DESCRIPTION:	Nu-Flame FR Colour Coat is a flame retardant paint finish. Also used as a basecoat for use prior to multi-coloured finishes.
ADVANTAGES:	Being a water soluble product this is safe for internal applications. Tested to BS 476 part 6 & 7 and satisfies Class '0' Requirements of current Building Regulations.
USES:	For use on walls and ceilings. Intermediate coat of the Nu-Flame Multi-coloured System.
COLOUR RANGE:	In any BS400 or RAL Shade.
PACK SIZE:	Single component product, supplied in 5 or 10 Litre cans.
VOLUME SOLIDS:	40%
COVERAGE RATE:	10 m ² per litre
DRYING TIME:	Touch :.....2 hours Overcoating.....4 hours
PREPARATION:	Ensure surfaces to be treated are clean, free from contamination and dry.
APPLICATION:	By brush/roller or spray. Should not be applied at temperatures below 5°C Or when relative humidity exceeds 85%.
EQUIPMENT CARE:	All equipment should be cleaned with water immediately after use
STORAGE:	Store away from direct sunlight and sources of heat. Protect from frost.
SHELF LIFE:	12 months (in original sealed container).
HEALTH & SAFETY:	Refer to health and safety sheets.



HYDRON
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494