

# PRODUCT DATA SHEET HPC 99

CI/SFB Vv4

January 2010

## NU-FLAME® FR COLOURCOAT

<b>DESCRIPTION:</b>	Nu-Flame FR Colour Coat is a flame retardant paint finish. Also used as a basecoat for use prior to multi-coloured finishes.
<b>ADVANTAGES:</b>	Being a water soluble product this is safe for internal applications. <b>Tested to BS 476 part 6 &amp; 7 and satisfies Class '0' Requirements of current Building Regulations.</b>
<b>USES:</b>	For use on walls and ceilings. Intermediate coat of the Nu-Flame Multi-coloured System.
<b>COLOUR RANGE:</b>	In any BS400 or RAL Shade.
<b>PACK SIZE:</b>	Single component product, supplied in 5 or 10 Litre cans.
<b>VOLUME SOLIDS:</b>	40%
<b>COVERAGE RATE:</b>	10 m <sup>2</sup> per litre
<b>DRYING TIME:</b>	Touch :.....2 hours Overcoating.....4 hours
<b>PREPARATION:</b>	Ensure surfaces to be treated are clean, free from contamination and dry.
<b>APPLICATION:</b>	By brush/roller or spray. Should not be applied at temperatures below 5°C Or when relative humidity exceeds 85%.
<b>EQUIPMENT CARE:</b>	All equipment should be cleaned with water immediately after use
<b>STORAGE:</b>	Store away from direct sunlight and sources of heat. Protect from frost.
<b>SHELF LIFE:</b>	12 months (in original sealed container).
<b>HEALTH &amp; SAFETY:</b>	Refer to health and safety sheets.



**HYDRON**  
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494