

# PRODUCT DATA SHEET **HPC 106 &107**

CI/SFB Vv4

January 2012

## **NU-FLAME® FR UNDERCOAT & GLOSS**

**DESCRIPTION:** Nu-Flame F. R. Undercoat and F.R. Gloss are oil based flame retardant paints for new and previously painted surfaces where a gloss finish is required.

**ADVANTAGES:** When Nu-Flame F. R. Undercoat and F.R. Gloss are used together. They provide a washable weather resistant finish for interior and exterior use. **Tested to BS 476 part 7 and passes Class 1 surface spread of flame**

**USES:** For use on door, skirting and other timber finishes. To complement the Nu-Flame wall finishes.

	<b>HPC 106 F. R. Undercoat</b>	<b>HPC 107 F. R. Gloss</b>
<b>COLOUR RANGE:</b>	Colour to suit finish	Any BS 4800 and RAL
<b>PACK SIZE:</b>	5 Litres	5 Litres
<b>COVERAGE RATE:</b>	10-12 m <sup>2</sup> per litre	10-12 m <sup>2</sup> per litre
<b>DRYING TIME:</b>	Touch dry.....4 hours. Overcoat.....16 hours.	Touch dry.....4 hours. Overcoat.....12 hours.

**PREPARATION:** Ensure surfaces to be treated are clean, free from contamination and dry.

**APPLICATION:** By brush/roller or spray  
Should not be applied at temperatures below 5°C  
Or when relative humidity exceeds 85%.

**EQUIPMENT CARE:** All equipment should be cleaned with water immediately after use

**STORAGE:** Store away from direct sunlight and sources of heat.  
Protect from frost.

**SHELF LIFE:** 12 months (in original sealed container).

**HEALTH & SAFETY:** Refer to health and safety sheets.



**HYDRON**  
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494