

## NU-FLAME® HEAT INSULATING BASECOAT

<b>DESCRIPTION:</b>	Nu-Flame Heat Insulating Basecoat is an intumescent basecoat developed to insulate flammable paint systems and control surface spread of flame and fire propagation.
<b>ADVANTAGES:</b>	When exposed to a fire Nu-Flame Heat Insulating Basecoat releases a flame extinguishing gas which instantly protects the surface. Simultaneously heat activates Nu-Flame Heat Insulating Basecoat underneath causing it to expand and create a fire protective barrier, insulating old paint films from heat and oxygen.
<b>USES:</b>	Nu-Flame Heat Insulating Basecoat is an intumescent undercoat for application to previously painted plaster, Artex, board, brick and concrete walls and ceilings. Overcoated with Nu-Flame F. R. Top Coat it insulates old paint films from fire, controlling the spread of flames along walls and ceilings.
<b>COLOUR RANGE:</b>	White / Pastel colours
<b>PACK SIZE:</b>	Single component product, supplied in 20 KG cans.
<b>VOLUME SOLIDS:</b>	60%
<b>COVERAGE RATE:</b>	8 m <sup>2</sup> per KG. 2 Coats Required
<b>DRYING TIME:</b>	Touch : .....4 hours Overcoat : .....8 hours.
<b>PREPARATION:</b>	Rub down old paints thoroughly. Ensure surfaces are sound to provide a key, wash down and allow to dry. Do not apply in damp, cold conditions or when condensation may form on walls and ceilings.
<b>APPLICATION:</b>	By brush/roller or Airless Spray
<b>EQUIPMENT CARE:</b>	All equipment should be cleaned with water immediately after use
<b>STORAGE:</b>	Store away from direct sunlight and sources of heat. Protect from frost.
<b>SHELF LIFE:</b>	12 months (in original sealed container).
<b>HEALTH &amp; SAFETY:</b>	Refer to health and safety sheets.



**HYDRON**  
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494