

PRODUCT DATA SHEET HPC 95

CI/SFB Vv4

January 2012

NU-FLAME® MULTI-COLOURED FEATURE COAT

DESCRIPTION:	Nu-Flame Multi-Coloured Feature will provide an attractive hard wearing decorative finish for internal communal areas.
ADVANTAGES:	Being a water soluble product this is safe for internal applications. Tested to BS 476 part 6 & 7 and satisfies Class '0' Requirements of current Building Regulations.
USES:	For use on walls and ceilings. Intermediate coat of the Nu-Flame Multi-coloured System.
COLOUR RANGE:	See colour card.
PACK SIZE:	Single component product. 4 litre supplied in 5 litre can. Add 1 litre of clean water.
VOLUME SOLIDS:	9%
COVERAGE RATE:	12 m ² per litre
DRYING TIME:	Touch :.....3 hours Overcoating.....6 hours
PREPARATION:	Ensure surfaces to be treated are clean, free from contamination and dry.
APPLICATION:	For best results use conventional spray equipment with an internal air mix. Nozzle diameter of 2.5 to 3 mm. and pressure of 20lbs/ sq. in.
EQUIPMENT CARE:	All equipment should be cleaned with water immediately after use
STORAGE:	Store away from direct sunlight and sources of heat. Protect from frost.
SHELF LIFE:	12 months (in original sealed container).
HEALTH & SAFETY:	Refer to health and safety sheets.



HYDRON
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494