

PRODUCT DATA SHEET HPC 94

CI/SFB Vv4

January 2012

NU-FLAME® S.P TACK PRIMER

DESCRIPTION:	Nu-Flame S.P. Tack Primer is a smooth, non-toxic, water-soluble primer, used as part of the Nu-Flame Fire Upgrade System.
ADVANTAGES:	Nu-Flame S.P. Primer provides excellent adhesion to previously painted surfaces prior to the application of Nu-Flame Heat Insulating Basecoat
USES:	Adhesion promoter for glazed and previously painted surfaces. Internal decorative paint system.
COLOUR RANGE:	White
PACK SIZE:	Single component product, supplied in 5 and 10 litre cans.
VOLUME SOLIDS:	40%
COVERAGE RATE:	10 m ² per litre.
DRYING TIME:	Touch :.....1 - 2 hours Overcoat :4 hours.
PREPARATION:	Ensure surfaces to be treated are clean, free from contamination and dry. Previously coated surfaces should be abraded
APPLICATION:	By brush/roller
EQUIPMENT CARE:	All equipment should be cleaned with water immediately after use
STORAGE:	Store away from direct sunlight and sources of heat. Protect from frost.
SHELF LIFE:	12 months (in original sealed container).
HEALTH & SAFETY:	Refer to health and safety sheets.



HYDRON
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494