

# PRODUCT DATA SHEET HPC 94

CI/SFB Vv4

January 2010

## NU-FLAME® S.P TACK PRIMER

|                             |   |
|-----------------------------|---|
| <b>DESCRIPTION:</b>         | Nu-Flame S.P. Tack Primer is a smooth, non-toxic, water-soluble primer, used as part of the Nu-Flame Fire Upgrade System.                     |
| <b>ADVANTAGES:</b>          | Nu-Flame S.P. Primer provides excellent adhesion to previously painted surfaces prior to the application of Nu-Flame Heat Insulating Basecoat |
| <b>USES:</b>                | Adhesion promoter for glazed and previously painted surfaces. Internal decorative paint system.   |
| <b>COLOUR RANGE:</b>        | White   |
| <b>PACK SIZE:</b>           | Single component product, supplied in 5 and 10 litre cans.  |
| <b>VOLUME SOLIDS:</b>       | 40%   |
| <b>COVERAGE RATE:</b>       | 10 m <sup>2</sup> per litre.  |
| <b>DRYING TIME:</b>         | Touch :.....1 - 2 hours<br>Overcoat : .....4 hours.   |
| <b>PREPARATION:</b>         | Ensure surfaces to be treated are clean, free from contamination and dry. Previously coated surfaces should be abraded                        |
| <b>APPLICATION:</b>         | By brush/roller   |
| <b>EQUIPMENT CARE:</b>      | All equipment should be cleaned with water immediately after use  |
| <b>STORAGE:</b>             | Store away from direct sunlight and sources of heat.<br>Protect from frost.   |
| <b>SHELF LIFE:</b>          | 12 months (in original sealed container).   |
| <b>HEALTH &amp; SAFETY:</b> | Refer to health and safety sheets.  |



**HYDRON**  
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494