

PRODUCT DATA SHEET

CI/SFB Vv4

January 2012

NU-FLAME® SINGLE COLOUR COATING SYSTEM

DESCRIPTION: Nu-Flame is a smooth, non-flammable, water soluble, single-colour coating system, providing a durable and protective finish to previously painted internal surfaces.

ADVANTAGES: Upgrades existing painted surfaces to Class '0' Optional graffiti resistant finish Water based for minimum hazard during application **Tested to BS 476 part 6 & 7 and satisfies Class '0' requirements of current Building Regulations.**

USES: Internal decorative paint system.

	HPC 94 SP TackPrimer	HPC 90 HeatInsulating Basecoat	ColourCoat
COLOUR RANGE:	Off White	See Colour Card	See Colour Card
PACK SIZE:	5 Litre	5 Litres	5 Litres
COVERAGE RATE:	1 coat @ 8-10 m ² per litre	2 coats @ 8 m ² per litre per coat	1 coat @ 8-10 m ² per litre
DRYING TIME:	4 hours	8 hours	4 hours

PREPARATION: Ensure surfaces to be treated are clean, free from contamination and dry. Previously coated surfaces should be abraded

APPLICATION: By brush/roller or spray

EQUIPMENT CARE: All equipment should be cleaned with water immediately after use

STORAGE: Store away from direct sunlight and sources of heat. Protect from frost.

SHELF LIFE: 12 months (in original sealed container).

HEALTH & SAFETY: Refer to health and safety sheets.



HYDRON
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494