

# PRODUCT DATA SHEET

CI/SFB Vv4

January 2010

## NU-FLAME® SINGLE COLOUR COATING SYSTEM

**DESCRIPTION:** Nu-Flame is a smooth, non-flammable, water soluble, single-colour coating system, providing a durable and protective finish to previously painted internal surfaces.

**ADVANTAGES:** Upgrades existing painted surfaces to Class '0' Optional graffiti resistant finish Water based for minimum hazard during application **Tested to BS 476 part 6 & 7 and satisfies Class '0' requirements of current Building Regulations.**

**USES:** Internal decorative paint system.

	<b>HPC 94 SP TackPrimer</b>	<b>HPC 90 HeatInsulating Basecoat</b>	<b>ColourCoat</b>
<b>COLOUR RANGE:</b>	Off White	See Colour Card	See Colour Card
<b>PACK SIZE:</b>	5 Litre	5 Litres	5 Litres
<b>COVERAGE RATE:</b>	1 coat @ 8-10 m <sup>2</sup> per litre	2 coats @ 8 m <sup>2</sup> per litre per coat	1 coat @ 8-10 m <sup>2</sup> per litre
<b>DRYING TIME:</b>	4 hours	8 hours	4 hours

**PREPARATION:** Ensure surfaces to be treated are clean, free from contamination and dry. Previously coated surfaces should be abraded

**APPLICATION:** By brush/roller or spray

**EQUIPMENT CARE:** All equipment should be cleaned with water immediately after use

**STORAGE:** Store away from direct sunlight and sources of heat. Protect from frost.

**SHELF LIFE:** 12 months (in original sealed container).

**HEALTH & SAFETY:** Refer to health and safety sheets.



**HYDRON**  
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494