

PRODUCT DATA SHEET HPC 25

CI/SFB Vv4

January 2012

NU-GUARD® CLEAR A.F

- DESCRIPTION:** Nu-Guard Clear AF Coating is a specially formulated single pack external coating designed to give effective protection against both fly-posting and graffiti.
- ADVANTAGES:** Posters will not adhere to the surface, once dry they will fall off or can be easily peeled off by hand. No scrapers or solvents are needed. Graffiti can be removed quick and easy by using warm soapy water.
- USES:** For use on street furniture such as traffic light control boxes, telephone, cable and electric junction boxes, CCTV and street lighting columns as well as brickwork, concrete and painted surfaces / murals.
- COLOUR RANGE:** Clear Gloss or Matt
- PACK SIZE:** Single component product, supplied in 5 and 20 litre cans.
- VOLUME SOLIDS:** 30-45%
- COVERAGE RATE:** 2 coats required. 10 m² per litre per coat.
- DRYING TIME:** Touch :1 - 2 hours
Overcoat :4 hours.
- PREPARATION:** Ensure surfaces to be treated are clean, free from contamination and dry. To prevent concrete surface darkening it is advisable to apply one coat of Nu-Guard WB Concrete Sealer.
- APPLICATION:** By brush/roller or spray. Should not be applied at temperatures below 5°C or when the relative humidity exceeds 85%.
- EQUIPMENT CARE:** All equipment should be cleaned with white spirit.
- STORAGE:** Store away from direct sunlight and sources of heat. Protect from frost.
- SHELF LIFE:** 12 months (in original sealed container).
- HEALTH & SAFETY:** Refer to health and safety sheets.



HYDRON
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494