

PRODUCT DATA SHEET HPC 05

CI/SFB Vv4

January 2010

NU-GUARD® A.G. HIGH SOLIDS FINISH

DESCRIPTION:	Nu-Guard A.G. is a siloxane-based coating with an excellent decorative appearance and outstanding resistance to solvents and chemicals, making it a first choice anti-graffiti coating for use on external surfaces.
ADVANTAGES:	Efficient graffiti removal with A.G.3 Graffiti Remover.
USES:	For use on a variety of substrates such as painted brickwork, render, concrete, metal and wood.
COLOUR RANGE:	Any BS4800 or RAL Shade
PACK SIZE:	Two component product, supplied in 1 and 5 litre units.
VOLUME SOLIDS:	90.00%
COVERAGE RATE:	16 m ² / Litre
DRYING TIME:	Touch :2 hours. Overcoat :3 hours.
PREPARATION:	Ensure surfaces to be treated are clean, free from contamination and dry
APPLICATION:	By brush/roller or spray. Should not be applied at temperatures below 5°C or when the relative humidity exceeds 85%.
EQUIPMENT CARE:	All equipment should be cleaned with Nu-Guard HS Thinners. Conventional thinners and brush cleaners are not effective.
STORAGE:	Store away from direct sunlight and sources of heat. Protect from frost.
SHELF LIFE:	12 months (in original sealed container).
HEALTH & SAFETY:	Refer to health and safety sheets.



HYDRON
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494