

# PRODUCT DATA SHEET HPC 02

CI/SFB Vv4

January 2010

## NU-GUARD® A.G. TACK PRIMER

<b>DESCRIPTION:</b>	Nu-Guard A.G. Tack Primer is a high performance water soluble, epoxy coating.
<b>ADVANTAGES:</b>	Provides first class adhesion to properly prepared surfaces
<b>USES:</b>	First coat of the Nu-Guard A.G. System. Developed to act as a tack primer over existing coatings and non porous substrates including glazed tiles.
<b>COLOUR RANGE:</b>	Off White
<b>PACK SIZE:</b>	Two component product, supplied in 5 litre units.
<b>VOLUME SOLIDS:</b>	40%
<b>COVERAGE RATE:</b>	8 m <sup>2</sup> / Litre
<b>DRYING TIME:</b>	Touch : .....3 - 4 hours. Overcoat : .....8 hours.
<b>PREPARATION:</b>	Ensure surfaces to be treated are clean, free from contamination and dry. Previously coated surfaces should be abraded.
<b>APPLICATION:</b>	By brush/roller or spray. Should not be applied at temperatures below 5°C or when the relative humidity exceeds 85%.
<b>EQUIPMENT CARE:</b>	All equipment should be cleaned with water immediately after use.
<b>STORAGE:</b>	Store away from direct sunlight and sources of heat. Protect from frost.
<b>SHELF LIFE:</b>	12 months (in original sealed container).
<b>HEALTH &amp; SAFETY:</b>	Refer to health and safety sheets.



**HYDRON**  
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494