

PRODUCT DATA SHEET HPC 230

CI/SFB Vv4

January 2012

SL2 - SHADOW LIFTING POULTICE

DESCRIPTION:	A specially formulated poultice cleaner for the removal of stubborn graffiti shadows from brickwork, stone and concrete.
ADVANTAGES:	Will effectively remove unsightly shadows remaining after graffiti removal.
COLOUR:	Straw coloured base and straw coloured liquid.
PACK SIZE	Supplied in 200 & 400 gramme kits
COVERAGE RATE	Should be applied to a thickness of 5–10 mm and covered with plastic with the edges taped to seal it.
PREPARATION:	Areas to be cleaned should be pre wetted with distilled water prior to application of SL2 to prevent streaking.
APPLICATION:	Apply the mixed SL2 with a wood or plastic spatula to the affected area and cover with plastic, with the edges taped to seal it. Allow the poultice to dry thoroughly, usually 24 hours. The drying out process is what pulls the stain out of the substrate and into the poultice. Remove the poultice from the stained with a wood or plastic spatula and rinse with distilled water. Repeat the process on persistent stubborn stains.
STORAGE:	Store away from direct sunlight and sources of heat. Protect from frost.
SHELF LIFE:	12 months (in original sealed container).
HEALTH & SAFETY:	Refer to health and safety sheets.



HYDRON
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494

PRODUCT DATA SHEET

CI/SFB



HYDRON
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494