



TECHNICAL DATA SHEET – HPC 08 NU-GUARD® AG COLOUR

THE ONE COAT WATER WASHABLE ANTI GRAFFITI COATING

DESCRIPTION:

Nu-Guard AG Colour Coating is a specially formulated single pack external coating designed to give effective protection against both fly-posting and graffiti.

ADVANTAGES:

A one coat application where graffiti will not adhere to the surface, once dry, graffiti can be removed quick and easy by using warm soapy water.

USES:

Most surfaces can be protected with just one coat of Nu-Guard AG Colour, giving quick application and protection from Graffiti and fly posting.

COLOUR RANGE:

Any RAL Colour.

PACK SIZE:

Single component product, supplied in 5 litre cans.

VOLUME SOLIDS:

70%

COVERAGE RATE:

One coat @ 8-10 m² / Litre
WFT – 125 microns
DFT – 90 microns

DRYING TIME:

Touch Dry :.....1-2 Hours.
Full Cure :.....6 Hours

PREPARATION:

Ensure surfaces to be treated are clean, free from contamination and dry. Application to very porous surfaces, it is advisable to apply one coat of Nu-Guard WB Concrete Sealer.

APPLICATION:

By brush/roller or spray.
Apply in one heavy coat.
Do not apply too thin.
Should not be applied at temperatures below 5°C or when the relative humidity exceeds 85%.

GRAFFITI REMOVAL:

Graffiti should be removed using warm soapy water. If using a pressure washer, no more than 70bar should be used.

EQUIPMENT CARE:

All equipment should be cleaned with white spirit.

STORAGE:

Store away from direct sunlight and sources of heat. Protect from frost. Do not allow moisture into the tin.

SHELF LIFE:

12 months (in original sealed container).

HEALTH & SAFETY:

Refer to MSDS

