

TECHNICAL DATA SHEET – HPC 125 NU-BASE WB EPOXY FLOOR FINISH

DESCRIPTION:

Nu-Base WB Epoxy Floor Finish is a two-pack water based resin. For use in most industrial floors including concrete and wood and provides a decorative dust-free finish. Being odour free and non-tainting is ideal for use in food industry, dairies, and breweries.

ADVANTAGES:

Nu-Base WB Epoxy Floor Finish has good chemical resistance. Will not support fungus or bacterial growth and is therefore suitable for application in food production areas, hospitals etc.

USES: FeRFA Class Type 2

Nu-Base WB Epoxy Floor Finish is suitable for us in garages, workshops, warehouses and general industrial usage.

COLOUR:

Selected colour range.

COVERAGE RATE:

7-8 m² / KG

DRYING TIMES

Touch dry	8 hours @ 20°C.
Overcoat	24 hours.
Full Cure	7 days.

POT LIFE:

1 – 1.5 Hours @ 20°C

VOLUME SOLIDS:

50 %

PACK SIZE

Two component product, supplied in 5 & 10 KG units.

PREPARATION:

All surfaces to be coated should be clean, dry and free from oil and grease etc. Ideally the substrate should be shot-blasted, mechanically abraded or acid etched with all loose, flaking materials and any laitance removed.

APPLICATION:

By brush/roller or airless spray.

EQUIPMENT CARE:

All equipment should be cleaned with water immediately after use.

STORAGE:

Recommended storage is in a cool, dry place with temperatures between 10-15 °C, and in accordance with the Highly Flammable Liquids and Liquefied Petroleum Gases Regulations 1972.

SHELF LIFE:

12 months (in original sealed container).

HEALTH & SAFETY:

Refer to MSDS