

## TECHNICAL DATA SHEET – HPC 129 NU-BASE CHLORINATED RUBBER

### DESCRIPTION:

Nu-Base Chlorinated Rubber Floor paint is a fast drying finish based on Chlorinated rubber resin, giving good adhesion and exterior durability.

### ADVANTAGES:

When fully dry, the paint has good resistance to petrol, paraffin and mineral oil spillage. Nu-Base Chlorinated Rubber Floor paint is ideally suited for brush or roller application over large areas.

### USES:

For use on metal and concrete.  
Ideal for use in swimming and paddling pools.

### COLOUR:

Selected colour range

### COVERAGE RATE:

10 – 12 m<sup>2</sup> per litre.

### DRYING TIMES

Touch dry.....30-45 Minutes@ 20°C.  
Overcoat.....12 hours.

### VOLUME SOLIDS

50%

### PACK SIZE

Single component product, supplied in 5 and 25 litre cans.

### PREPARATION:

All surfaces to be coated should be clean, dry and free from oil and grease etc. Ideally the substrate should be shot-blasted, mechanically abraded or acid etched with all loose, flaking materials and any laitance removed.

### APPLICATION:

By brush/roller. Paints should be used as supplied, thinning is not recommended.

### EQUIPMENT CARE:

All equipment should be cleaned with Nu-Base Chlorinated Rubber Thinners. Conventional thinners and brush cleaners are not effective.

### STORAGE:

Recommended storage is in a cool, dry place with temperatures between 10-15°C, and in accordance with the Highly Flammable Liquids and Liquefied Petroleum Gases Regulations 1972.

### SHELF LIFE:

12 months (in original sealed container).

### HEALTH & SAFETY:

Refer to MSDS