

## TECHNICAL DATA SHEET – HPC 136 NU-BASE ACRYLIC BLOCK SEAL

### DESCRIPTION:

Nu-Base Acrylic Block Seal is a specifically formulated quick drying acrylic sealant designed to protect concrete and block paving against the ingress of water, dirt, oil, grease and a wide range of chemicals.

### ADVANTAGES:

Single pack ready for immediate use. Will consolidate jointing sand and help stop the growth of moss and weeds, and will provide a cost effective hard wearing, quick drying, durable and chemical resistant finish.

### USES:

Nu-Base Acrylic Block Seal is for use on concrete and block paving.

### COLOUR:

Clear.

### COVERAGE RATE:

This is dependent upon the surface porosity. Average coverage rate is in the region of 3-5 m<sup>2</sup> per litre.

### DRYING TIMES

Touch dry.....40 Minutes@ 20°C.  
Overcoat.....1 hour.

### PACK SIZE

Single component product, supplied in 25 litre cans.

### PREPARATION:

Ensure surfaces to be treated are clean, free from contamination and dry. All loose materials should be swept away and laitance removed by etching with Nu-Base Acid Etch. The surface should then be washed off to provide a clean neutral surface and allowed to dry overnight.

### APPLICATION:

By brush/roller or low pressure spray

### EQUIPMENT CARE:

All equipment should be cleaned with Xylene. Conventional thinners and brush cleaners are not effective.

### STORAGE:

Store away from direct sunlight and sources of heat. Protect from frost.

### SHELF LIFE:

12 months (in original sealed container).

### HEALTH & SAFETY:

Refer to MSDS